

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SikaTop®-Seal 107 Elastik Part A

1.2 Relevant identified uses of the substance or mixture and uses advised against

1.3 Details of the supplier of the safety data sheet

Company name of supplier : Sika Yapi Kimyasallari A.S.
İstanbul Deri Organize Sanayi Bölgesi 2. yol
J-7 Parsel / Aydınlı Orhanlı Mevkii
34944 Tuzla / İstanbul
Turkey
Telephone : +90 216 581 06 00
Telefax : +90 216 581 06 99
E-mail address of person : bilgi@tr.sika.com
responsible for the SDS

1.4 Emergency telephone number

+90 216 581 06 00 / 1260
Ulusal Zehir Danışma Merkezi (UZEM): 114

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Type of product : Mixture

Classification T.R. SEA No 28848

Skin sensitisation, Category 1 H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling T.R. SEA No 28848

Hazard pictograms :



Signal word : Warning

Hazard statements : H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves.
Response: P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
Disposal: P501	Dispose of contents/container in accordance with local regulation.

Hazardous components which must be listed on the label:

1,2-benzisothiazol-3(2H)-one (BIT)

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No.	T.R. SEA No 28848	Concentration (% w/w)
1,2-benzisothiazol-3(2H)-one (BIT)	2634-33-5 220-120-9	Acute Tox.4; H302 Acute Tox.2; H330 Skin Irrit.2; H315 Eye Dam.1; H318 Skin Sens.1; H317 Aquatic Acute1; H400 Aquatic Chronic2; H411	$\geq 0,0025$ - $< 0,025$
mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M)IT/MIT (3:1))	55965-84-9	Acute Tox.3; H331 Acute Tox.2; H310 Acute Tox.3; H301 Skin Corr.1B; H314 Skin Sens.1A; H317 Aquatic Acute1; H400 Aquatic Chronic1; H410	$\geq 0,0015$ - $< 0,0025$
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). :			
4. (1,1,3,3-tetramethylbutyl) phenol, ethoxylated	9002-93-1	Aquatic Chronic3; H412	$\geq 0,25$ - < 1

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

SECTION 4: First aid measures

4.1 Description of first aid measures

- | | |
|-------------------------|---|
| General advice | : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance. |
| If inhaled | : Move to fresh air.
Consult a physician after significant exposure. |
| In case of skin contact | : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician. |
| In case of eye contact | : Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist. |
| If swallowed | : Do not induce vomiting without medical advice.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person. |

4.2 Most important symptoms and effects, both acute and delayed

- | | |
|----------|--|
| Symptoms | : Allergic reactions
See Section 11 for more detailed information on health effects and symptoms. |
| Risks | : sensitising effects
May cause an allergic skin reaction. |

4.3 Indication of any immediate medical attention and special treatment needed

- | | |
|-----------|--------------------------|
| Treatment | : Treat symptomatically. |
|-----------|--------------------------|

SECTION 5: Firefighting measures

5.1 Extinguishing media

- | | |
|------------------------------|--|
| Suitable extinguishing media | : In case of fire, use water/water spray/water jet/carbon dioxide/sand/foam/alcohol resistant foam/chemical powder for extinction. |
|------------------------------|--|

5.2 Special hazards arising from the substance or mixture

- | | |
|----------------------------|--|
| Hazardous combustion prod- | : No hazardous combustion products are known |
|----------------------------|--|

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

ucts

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.
Deny access to unprotected persons.

6.2 Environmental precautions

Environmental precautions : Do not flush into surface water or sanitary sewer system.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products

Advice on protection against : Normal measures for preventive fire protection.

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

fire and explosion

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully re-sealed and kept upright to prevent leakage. Store in accordance with local regulations.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : Consult most current local Product Data Sheet prior to any use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166
Eye wash bottle with pure water

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard must be worn at all times when handling chemical products. Reference number EN 374. Follow manufacturer specifications.

Suitable for short time use or protection against splashes:
Butyl rubber/nitrile rubber gloves (0,4 mm)
Contaminated gloves should be removed.
Suitable for permanent exposure:
Viton gloves (0.4 mm),
breakthrough time >30 min.

Skin and body protection : Protective clothing (e.g. Safety shoes acc. to EN ISO 20345, long-sleeved working clothing, long trousers). Rubber aprons and protective boots are additionally recommended for mixing and stirring work.

Respiratory protection : Respirator selection must be based on known or anticipated

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

exposure levels, the hazards of the product and the safe working limits of the selected respirator.

organic vapor filter (Type A)

A1: < 1000 ppm; A2: < 5000 ppm; A3: < 10000 ppm

Ensure adequate ventilation. This can be achieved by local exhaust extraction or by general ventilation. (EN 689 - Methods for determining inhalation exposure). This applies in particular to the mixing / stirring area. In case this is not sufficient to keep the concentrations under the occupational exposure limits then respiration protection measures must be used.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: white
Odour	: characteristic
Odour Threshold	: No data available
Flash point	: Not applicable
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Lower explosion limit (Vol-%)	: No data available
Upper explosion limit (Vol-%)	: No data available
Flammability	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
pH	: No data available
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapour pressure	: 23 hPa
Density	: 1 g/cm ³ at 20 °C
Water solubility	: No data available

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

Partition coefficient: n-octanol/water	:	No data available
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 7 mm ² /s at 40 °C
Relative vapour density	:	No data available
Evaporation rate	:	No data available

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

The product is chemically stable.

10.3 Possibility of hazardous reactions

Hazardous reactions : No hazards to be specially mentioned.

10.4 Conditions to avoid

Conditions to avoid : No data available

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Acute oral toxicity : LD50 Oral (Rat): 597 mg/kg

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2.000 mg/kg

4. (1,1,3,3-tetramethylbutyl) phenol, ethoxylated:

Acute oral toxicity : LD50 Oral (Rat): > 4.000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

SECTION 12: Ecological information

12.1 Toxicity

Components:

1,2-benzisothiazol-3(2H)-one (BIT):

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 3 mg/l
Exposure time: 48 h

mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) (C(M):

M-Factor (Short-term (acute) aquatic hazard) : 100

M-Factor (Long-term (chronic) aquatic hazard) : 10

4. (1,1,3,3-tetramethylbutyl) phenol, ethoxylated:

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): ca. 1,8 mg/l
Exposure time: 96 h

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : There is no data available for this product.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The generation of waste should be avoided or minimized wherever possible.
Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way.
Dispose of surplus and non-recyclable products via a licensed waste disposal contractor.
Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Contaminated packaging : 15 01 10* packaging containing residues of or contaminated by dangerous substances

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

No data available

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors	: Not applicable
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: 4. (1,1,3,3-tetramethylbutyl) phenol, ethoxylated
REACH - List of substances subject to authorisation (Annex XIV)	: 4. (1,1,3,3-tetramethylbutyl) phenol, ethoxylated
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	: Not applicable
Regulation (EC) No 850/2004 on persistent organic pollutants	: Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals	: Not applicable
KKDIK (30105 (Bis)) - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex 17)	: See Annex 17 to KKDIK Regulation No.30105 (Bis) (23.06.2017) for Conditions of restriction

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: (3)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
Not applicable

Volatile organic compounds : Law on the incentive tax for volatile organic compounds (VOCV)
Volatile organic compounds (VOC) content: < 0,01 %
Remarks: no VOC duties

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,01 %, 0,12 g/l
Remarks: VOC content excluding water

Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: < 0,01 %, 0,06 g/l
Remarks: VOC content valid only for coating materials used on wood surfaces

Other regulations : According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".
Regulation on Classification, Labelling and Packaging of Substances and Mixtures. Dated 11 December 2013, Numbered 28848 (Bis) Ministry of Environment and Forestry.

SECTION 16: Other information

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H330 : Fatal if inhaled.
H331 : Toxic if inhaled.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
ADR	: European Agreement concerning the International Carriage of Dangerous Goods by Road
CAS	: Chemical Abstracts Service
DNEL	: Derived no-effect level
EC50	: Half maximal effective concentration
GHS	: Half maximal effective concentration
IATA	: International Air Transport Association
IMDG	: International Maritime Code for Dangerous Goods
LD50	: Median lethal dose (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals)
LC50	: Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)
MARPOL	: International Convention for the Prevention of Pollution from Ships, 1973 as modified by the Protocol of 1978
OEL	: Occupational Exposure Limit
PBT	: Persistent, bioaccumulative and toxic
PNEC	: Predicted no effect concentration
REACH	: Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency
SVHC	: Substances of Very High Concern
vPvB	: Very persistent and very bioaccumulative

Classification of the mixture:

Skin Sens. 1 H317

Classification procedure:

Calculation method

SDS Author

Atilim Yetiskin
yetiskin.atilim@tr.sika.com
+902165810647
Certification number; gbf01.13.06
certification date ; 24.03.2018

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

SAFETY DATA SHEET

According to 13 December 2014, No:29204, "Ministry of Environment and Urbanization; Regulation on Safety data sheets regarding hazardous substances and mixtures".



SikaTop®-Seal 107 Elastik Part A

Revision Date 19.10.2018

Version 1.0

Print Date 19.10.2018

TR / EN