



PRODUCT DATA SHEET

Sikacryl®-300 Ekstra Silikonize Mastik

Acrylic based sealant for interior use

DESCRIPTION

Sikacryl®-300 Extra is a 1-part, acrylic, water-based joint sealant for internal joints.

USES

- Connections around window and door frames
- Connection joints of prefabricated building elements
- It is used in joints between skirting boards, wall connections, to fill superficial cracks before painting.

FEATURES

- Good adhesion to many construction materials
- Easy to apply
- Over-paintable
- Internal use

CERTIFICATES AND TEST REPORTS

CE Marking and Declaration of Performance to EN15651-1 - Sealants for interior application

PRODUCT DATA SHEET

Sikacryl®-300 Ekstra Silikonize Mastik

Kasim 2024, Version 02.01

02051404000000154

PRODUCT INFORMATION

Composition	1 part-acrylic
Packaging	447 g cartridge (24 cartridges per box) 632 g/400 ml and 948 g/600 ml foil packs (20 foil packs per box)
Colour	White, black, brown, anthracite etc. For other colours please contact the local sales organisation.
Shelf life	18 months from date of production
Storage conditions	The product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +25 °C. Always refer to packaging.
Density	~1,54 kg/l (CQP 006)

TECHNICAL INFORMATION

Shore A hardness	~50 (after 28 days) (CQP 023)
Tensile strength	0,2 N/mm ² (CQP 36)
Joint design	The joint dimensions must be designed to suit the movement capability of the sealant. The joint width must be ≥ 10 mm and ≤ 20 mm. A width to depth ratio of 2:1 must be maintained. Triangular joint profiles must have sides for bonding ≥ 7 mm.
Elongation at break	~140% (CQP 36)

APPLICATION INFORMATION

Ambient air temperature	+5 °C to +30 °C, min. +3 °C above dew point temperature.
Skimming time	~20-35 minutes (+23 °C / 50 % r.h.)

BASIS OF PRODUCT DATA

All technical data stated in this Data Sheet are based on laboratory tests. Actual measured data may vary

due to circumstances beyond our control.

FURTHER DOCUMENTATION

- Pre-treatment Sealing and Bonding Chart

PRODUCT DATA SHEET
Sikacryl®-300 Ekstra Silikonize Mastik
Kasim 2024, Version 02.01
02051404000000154

BUILDING TRUST



IMPORTANT CONSIDERATIONS

- Colour variations may occur due to the exposure in service to chemicals, high temperatures and/or UV radiation (especially with white colour shade). This effect is aesthetic and does not adversely influence the technical performance or durability of the product.
- Sikacryl®-300 Extra can be over-painted with most conventional facade paint coating systems. However, paints must first be tested to ensure compatibility by carrying out preliminary trials (e.g. according to ISO technical paper: Paintability and Paint Compatibility of Sealants). Optimum results are obtained when the sealant is allowed to fully cure first. Note: non-flexible paint systems may impair the elasticity of the sealant and lead to cracking of the paint coating.
- Do not use on bituminous substrates, natural rubber, EPDM rubber or on any building materials which might leach oils, plasticisers or solvents that could degrade the sealant.
- Do not use as a glass sealant, for floor or sanitary joints, on marble, natural stone or on civil engineering structures.
- Do not use for joints under water pressure or permanent water immersion.
- Application during high temperature changes is not recommended (movement during curing).

ECOLOGY, HEALTH AND SAFETY

User must read the most recent corresponding Safety Data Sheets (SDS) before using any products. The SDS provides information and advice on the safe handling, storage and disposal of chemical products and contains physical, ecological, toxicological and other safety-related data.

PRODUCT DATA SHEET

Sikacryl®-300 Ekstra Silikonize Mastik
Kasim 2024, Version 02.01
02051404000000154

APPLICATION INSTRUCTIONS

SUBSTRATE PREPARATION

The substrate must be clean, dry, sound and free from oils, grease, dust and loose or friable particles. Sikacryl®-300 Extra adheres without primers and/or activators. On plastics and paints, adhesion tests must be carried out prior to application. Iron and steel must be protected with an anti-corrosion primer.

MIXING

1-part ready to use

APPLICATION METHOD / TOOLS

It is recommended to use masking tape where neat or exact joint lines are required. Remove the tape within the skinning time after finishing. Sikacryl®-300 Extra is supplied ready to use. Prepare the end of the cartridge, insert into the sealant gun and fit the nozzle. Extrude Sikacryl®-300 Extra into the joint or around the connection ensuring that it comes into full contact with the sides of the joint or connecting surfaces and avoiding any air entrapment. After application, sealant must be firmly tooled against the joint sides to ensure adequate adhesion and a smooth finish. Use water to smooth the joint surface. Do not use tooling products containing solvents.

CLEANING OF EQUIPMENT

Clean all tools and application equipment with water immediately after use. Hardened material can only be removed mechanically.

LOCAL RESTRICTIONS

Note that as a result of specific local regulations the declared data and recommended uses for this product may vary from country to country. Consult the local Product Data Sheet for exact product data and uses.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

PRODUCT DATA SHEET

Sikacryl®-300 Ekstra Silikonize Mastik

Kasım 2024, Version 02.01

02051404000000154

